

	PRODUCT SPECIFICATION
	Mosquito Netting 18 x 16 Stiff

DINXPERLO Datasheet nr. FG1816S

Subject	Mosquito netting stiff
Application	Protection against insects
Material	Fiberglass
Weave pattern	Plain
Mesh count	18 x 16
Apertures per 100 x 100 mm	69 (tol.±0.5) x 61 (tol.±2)
Aperture	1.17 x 1.35 mm.
Transparency	more than 66%
Yarn diameter	0.28 mm equals 95 tex
Yarn composition	Endless multiple glassfilaments with a PVC coating.
Glassweight	more than 38%
Tear strength yarn	more than 11 Newton per yarn
Colours	Gray, white, green, aqua-green, beige, charcoal, terra-cotta, orange and colours to costumers specification
Weight	125 grams per m ²
Thickness	0.35 mm
Temperature-resistance	minus 25 degrees Centigrade up to 80
Flame resistance	M2 or better
Stiffness	Stiff quality with Gurley value of 250 x 190 (tol.±35) in warp and weft

Delivery form and rollappearance:

Width of the roll	Optional (max. 2.60 m)
Widthtolerance	-0/+3 mm
Length of the roll	Max. 6 m
Wrapping tube	42, 71 or 76 mm inside diameter
Selvages	Cut selvages
Perpendicularity	Max. deviation 12 mm per meter
Flatness	A piece of 1000 x 1000 mm shall not raise more than 5 mm from the table in relaxed condition.